

Inverters

TECHNICAL SPECIFICATIONS

Series	Model Name	Rating	Input voltage range	Maximum Charging Current	Net Weight (In Kg)	Dimension (LXWXH) In CM	Protection
Eco Watt Neo	Eco Watt Neo 700	600VA	100V-290V	13A	7.4 kg	27.5x26x11.5	Low Battery, Short Circuit, Overload, Over Charge, Deep Discharge, Over Temperature, AC MCB*
	Eco Watt Neo 800	700VA	100V-290V	14A	7.8 kg	27.5x26x11.5	
	Eco Watt Neo 900	800VA	100V-290V	14A	8.4 kg	27.5x26x11.5	
	Eco Watt Neo 1050	900VA	100V-290V	17A	9.3 kg	27.5x26x11.5	
	Eco Watt Neo 1250 Pro	1100VA	85V-290V	17A	10.4 kg	27.5x30.2x13	
	Eco Watt Neo 1650	1500VA	100V-290V	17A	14.5 kg	27.5x30.2x13	
	Eco Watt Neo 2300	2000VA	90V-290V	20A	17.7 kg	40x31.1x15.2	
Eco Volt Neo	Eco Volt Neo 750	650VA	85V-290V	14A	6.8 kg	27.5x26x11.5	Low Battery, Short Circuit, Overload, Over Charge, Deep Discharge, Over Temperature & MCB*
	Eco Volt Neo 850	700VA	85V-290V	14A	7.4 kg	27.5x26x11.5	
	Eco Volt Neo 1050	900VA	85V-290V	17A	9.5 kg	27.5x26x11.5	
	Eco Volt Neo 1250	1100VA	85V-290V	17A	13 kg	27.5x30.2x13	
	Eco Volt Neo 1550	1400VA	85V-290V	17A	13.5 kg	27.5x30.2x13	
	Eco Volt Neo 1650	1500VA	85V-290V	17A	14 kg	27.5x30.2x13	
	Eco Volt Neo 2300	2000VA	85V-290V	20A	17.9 kg	40x31.1x15.2	
Icon	Icon 1100	900VA	85V-290V	17A	13 kg	76.5x24.6x50.5	Low Battery, Short Circuit, Overload, Over Charge, Deep Discharge, Over Temperature & MCB*
	Icon 1600	1400VA	85V-290V	21A	16.8 kg	76.5x24.6x50.5	
Zelio Smart	Zelio Smart 1100	900VA	110V-285V	15A	10 kg	27.5x24.8x12	Overload, Low Battery, Over Charge, Short Circuit, Over Temperature & Wrong Wiring



Series	Model Name	Rating	Input voltage range	Maximum Charging Current	Net Weight (In Kg)	Dimension (LXWXH) (in CM)	Protection
Shakti Charge & Eco Watt Rapid	Shakti Charge 1150	900VA	90V-290V	16A	9.9 kg	40.2x24x13.2	Overload, Short-circuit, Battery Deep Discharge, Low Battery, Overcharge
	Shakti Charge 1450	1100VA	90V-290V	20A	11.1 kg	40.2x24x13.2	
	Eco Watt XL Rapid 1650	1500VA	90V-290V	27A	14.6 kg	40.2x32x15	
Optimus	Optimus 1250+	1100VA	85V-285V	18A	11.4 kg	30.5x27.5x13.9	Deep Discharge, Overload, Short-circuit, Over Temperature MCB
	Optimus 2300+	2000VA	85V-285V	21A	21 Kg	30x32.6x28.4	
	Optimus 2800+	2500VA	85V-285V	21A	22.5 kg	30x32.6x28.4	
	Optimus 3800+	3500VA	85V-285V	21A	31.5 kg	30x41.7x45.2	
Power Pro	Power Pro 2250	2000VA	90V-290V	20A	20.2 kg	40x33x16.5	Low Battery, Reverse Polarity, Short Circuit, Overload, Over Charge, Deep Discharge, Over Temperature & MCB
iCruze	iCruze 5000+	4000VA	140V-280V	21A	36 kg	30x47.1x45	Low Battery, Reverse Polarity, Short Circuit, Overload, Over Charge, Deep Discharge, Over Temperature, DC & AC MCB
	iCruze 6000+	5500VA	140V-280V	21A	36 kg	30x36.6x42.5	
	iCruze 7000+	6000VA	140V-280V	21A	48 kg	30x36.6x42.5	
	iCruze 9000+	7500VA	140V-280V	21A	71.62 kg	30x47.1x56	
	iCruze 11000+	10000VA	140V-280V	21A	77.8 kg	30x47.1x56	
Li-On	Li-On 1250	1100VA	95V-285V	21A	25 kg	30x35.5x28.4	Low Battery Pre-Alarm, Overload & short circuit, DC MCB